memory (RAM) and read only memory (ROM). The module 201 also includes an number of input/output (I/O) interfaces including an audio-video interface 207 that couples to the video display 214 and loudspeakers 217, an I/O interface 213 for the keyboard 202 and mouse 203 and optionally a joystick (not illustrated), and an interface 208 for the modem 216 and printer 215. In some implementations, the modem 2116 may be incorporated within the computer module 201, for example within the interface 208. A storage device 209 is provided and typically includes a hard disk drive 210 and a floppy disk drive 211. A magnetic tape drive (not illustrated) may also be used. A CD-ROM drive 212 is typically provided as a non-volatile source of data. The components 205 to 213 of the computer module 201, typically communicate via an interconnected bus 204 and in a manner which results in a conventional mode of operation of the computer system 200 known to those in the relevant art. Examples of computers on which the described arrangements can be practised include IBM-PC's and compatibles, Sun Sparcstations or alike computer systems evolved therefrom.

[0094] Typically, the application program is resident on the hard disk drive 210 and read and controlled in its execution by the processor 205. Intermediate storage of the program and any data fetched from the network 220 may be accomplished using the semiconductor memory 206, possibly in concert with the hard disk drive 210. In some instances, the application program may be supplied to the user encoded on a CD-ROM or floppy disk and read via the corresponding drive 212 or 211, or alternatively may be read by the user from the network 220 via the modem device 216. Still further, the software can also be loaded into the computer system 200 from other computer readable media. The term "computer readable medium" as used herein refers to any storage or transmission medium that participates in providing instructions and/or data to the computer system 200 for execution and/or processing. Examples of storage media include floppy disks, magnetic tape, CD-ROM, a hard disk drive, a ROM or integrated circuit, a magneto-optical disk, or a computer readable card such as a PCMCIA card and the like, whether or not such devices are internal or external of the computer module 201. Examples of transmission media include radio or infra-red transmission channels as well as a network connection to another computer or networked device, and the Internet or Intranets including e-mail transmissions and information recorded on Websites and the like.

[0095] The method 100 of editing a document may alternatively be implemented in dedicated hardware such as one or more integrated circuits performing the functions or sub functions of the method 100. Such dedicated hardware may include graphic processors, digital signal processors, or one or more microprocessors and associated memories.

[0096] As will be explained in detail below, the method 100 is executed when a user creates a document (i.e., a digital photo album) and associated layout on the computer 200, for example. The document and the associated layout can be published over the network 220 to a list of one or more recipients (i.e., a PUBLISH event) configured within the document. These recipients are hereinafter referred to as collaborators. Some or all of the collaborators can modify (i.e., further enhance) the layout of the published photo album and publish the modifications (i.e., a MODIFY event) over the network 220. During the execution of the method

100, one or more of the collaborators may log in and/or out of an editing session for the document on the network 220 (i.e., LOGIN and LOGOUT events).

[0097] While the collaborators are logged into the current editing session they are referred to as active collaborators. A list of active collaborators (ie., those collaborators currently logged into a current editing session for the document) is preferably configured within memory 206. The receipt of the published document and any modifications thereto can be acknowledged by the collaborators of the originally published document (i.e., ACK\_DOC and ACK\_MODIFY events). Subsequently, simultaneous modifications to the published document can be merged with the originally published document.

[0098] The method 100 of editing a document is preferably implemented as software resident on the hard disk drive 210 and being controlled in its execution by the processor 205. The method 100 begins at step 101, where the processor 205 detects a request (i.e., a message) entered via the keyboard 202 or mouse 203 or received over the network 220 from another computer (e.g., servers 295, 299) connected to the network 220. Upon receiving such a message, the method 100 proceeds to step 103, where the message is examined by the processor 205 to determine the source of the message. If the message originates from the keyboard 202 or mouse 203, then the method 100 proceeds to step 107. Otherwise, if the message originated from the network 220, then the method 100 proceeds to step 105, where the processor 205 processes the network message and then returns to step 101. A method 300 for processing the network message as executed at step 105 will be explained below with reference to FIG. 3.

[0099] At step 107, if the processor 205 determines that the document (i.e., a photo album) is to be published (i.e., a PUBLISH message is detected) then the method 100 proceeds to step 110. At step 110 the document is transmitted to one or more collaborators as will be described below with reference to FIG. 11, and execution returns to step 101. The published document includes information, hereinafter referred to as 'version information', embedded therein. The version information includes a version string identifying the current version of the document. The version information can also indicate the name (i.e., a username) of the author of the document, which of the collaborators have acknowledged receiving the latest version of the document, and the UUID (i.e., a universally-unique identifier) of the document. The UUID of the document is the same for each of the versions of a document (i.e., the original document and a modified version of the original document both have the same UUID albeit with a different version number).

[0100] If the processor 205 determines that the document is to be modified (i.e., a MODIFY message is detected), at step 107, then execution proceeds to step 112. At step 112, the processor 205 transmits a patch representing a modification to the document, over the network 220 to one or more collaborators as will described below with reference to FIG. 12, and execution returns to step 101.

[0101] Any modifications to the originally published document made by one or more of the collaborators listed within the document can be subsequently merged. In accordance with the method 100, a distinction is made between the merging of simultaneous modifications to the document